

Purlogix™ 2000 series point-of-use water filtration coolers are the premier drinking water solution for any office or commercial environment.

- Enjoy a continuous supply of ice-cold or piping-hot filtered water.
- Choose White or Black to match any decor.
- Ergonomically designed with raised faucet area that accommodates tall glasses and sport bottles.
- High capacity stainless steel cold and hot tanks.
- Available in a variety of filtration configurations to meet your specific water filtration needs.
- Optional Ultraviolet Disinfection for maximum protection.



**ULTRAVIOLET
PROTECTION**

The Purely Logical Choice


Features

- Available in black or white (black available only in PBV-2000 model)
- Ultraviolet Cooling Tank Bio-Film Control Option
- Mechanical faucets (safety hot)
- Sleek appliance appearance with raised faucet height
- Large faucet area for sport bottles and glasses
- High Capacity Stainless Cold Tank
- High Capacity Stainless Hot Tank
- Primary and secondary floats
 - Primary electronic water shut-off system
 - Secondary mechanical safety shut-off system
- Adjustable leveling feet
- LED indicator panel
- Drip tray with knock-out for drain
- Heavy gauge powder coated side panels
- Solid state circuit board with microprocessor control
- Adjustable cold control (38° to 46° F)
- Provides filtered water for coffee brewer or accessory item




Options

4-Vessel RO
Sediment Filter
Pre-Carbon Filter
80 GPD TFC RO
Post-Carbon Filter



2-Vessel
Micro Filtration
Sediment Filter
Carbon Multi-Stage
Micro Filter



UV Disinfection
Optional In-Tank
Ultraviolet (UV)
Disinfection



For maximum flexibility, Purlogix™ offers systems with RO, Micro Filtration or without filters. Optional In-Tank Ultraviolet (UV) Disinfection is available on all models.

ULTRAVIOLET PROTECTION

MODELS		*PRV-2000, PR-2000	*PMV-2000, PM-2000	*PBV-2000, PB-2000
INPUT VOLTAGE		120V AC, 60Hz **		
POWER CONSUMPTION	COMPRESSOR	100W		
	HEATER	460W		
TANK CAPACITY	COLD	1.3 Gallons with 0.8 Gallons Chilled		
	HOT	0.8 Gallons (No Hot on PBV-2000C)		
FILTRATION SYSTEMS		80 GPD Reverse Osmosis	Sediment & Carbon MF	No System Installed
DIMENSIONS		11.8"W x 16.5"D x 49.2"H		
WEIGHT		77 lbs.	75 lbs.	73 lbs.

*Includes In-Tank UV **Systems also available in 220V 50Hz

Purlogix™